

Fingerprint Time Attendance

C280 Series



Features:

- World-class algorithm, high-speed and accurately identify fingerprint.
- Fingerprint/Pin/Card authentication.
- Suitable for the entrances and exits of office, factory, hotel, school, etc.
- Large capacity, user capacity upto 2000, logs capacity upto 120000.
- 2.8 inch TFT screen 320x240 pixel.
- TCP/IP + USB Flash Drive Download + USB Communication.
- More helpful function like T9 input method, self-service inquiry, etc.



Specification

Model	C280A	C280B/C
Max. user	2,000	Up to 8,000
Fingerprint template capacity	2,000 (up to 8,000)	Up to 8,000
Log capacity	160,000	160,000
Password capacity	2,000	Up to 8,000
Card capacity (optional)	2,000	Up to 8,000
RF card (optional)	125kHz EM / 13.56MHz Mifare	
Sensor type	Optical, work outdoor well avoid direct sunlight	
Access mode	Fingerprint or Password or Card or Fingerprint+Password or Card+Password or Fingerprint+Card+Password	
Interface	TCP/IP, USB (host and slave), relay (access contro, optional)	
LCD display	2.8" TFT color screen 320x240 pixel	
Voice instruction	16-bit Hi-Fi voice & sound indication	
Language	English	
Verification time	< 1 second [1:N]	
FRR (False Rejection Rate)	< 1%	
FAR (False Acceptance Rate)	< 0.0001%	
Power source	5VDC/1A	
Access control	Optional	
External backup battery	Optional	
Operating temperature	0°C-45°C	
Operating humidity	<90%RH	
Dimensions (mm)	195 x 135 x 43	
Weight (kg)	0.5	
Quantity/Carton	10 units	
Gross weight/carton (kg)	9.7	
Carton size	550 x 250 x 522	
Quantity / container	3800 units per 20' container	

Box contents

C280	x 1 pc
Power adapter	x 1 pc
USB cable	x 1 pc
manual CD	x 1 pc
Installation accessories	x 1 set